

# UTX

U-Trough Auger



Built with resilience and longevity in mind – able to withstand the harshest physical demands



FEATURES

- **Wear Edge Technology™** extends the life of the flighting
- Durable **Powder Coat Paint** protects the auger finish and repels rust
- **Removeable Tow Bar** easily connects and detaches from the hitch
- **Solid Tube Guard** completely encloses the driveline
- **Square One-Bolt Flight Connections** provide improved performance through positive torque transfer for smooth operation
- **Hydraulic Winch** helps raise and lower the auger with ease and precision
- **Triple Banded Belts** maintain speed by providing better tension with less slippage
- Sealed, grease-lubricated **Top Drive** comes with forged steel sprockets and heavy-duty chain, both protected by durable cover and designed to match the auger capacity
- **Top Drive Chain Tensioner** provides better adjustment capabilities and consistent chain drive tension
- **Driveshaft and Bearings** are constructed of durable oil impregnated hardwood for long, quiet operation and can be easily replaced without disassembling the driveshaft
- **Hose Routing** provides a cleaner, sleeker look, while protecting the hoses from the elements



REVERSING GEARBOX

Comes with shifting linkage and lockout, allowing the operator to safely reverse the auger at all angles.



COLLAPSING SPRING LOADED HOPPER EXTENSION

Quickly and easily fit under some of your lowest and hardest to reach bin unloads and hopper bins.



HEAVY-DUTY SELF-PROPELLED MOVER KIT WITH JOYSTICK HYDRAULIC STEERING

The heavy-duty, self-propelled mover makes setting up at bins and moving around the yard fast and easy, so you can get the job done in less time.



GAS MOTOR

Choose either a Vanguard or Kohler gas motor, with a large 44-liter gas tank that lets you work as long as you need to.



WORK LIGHTS


LED work lights allow you to work later so you can get the job done sooner.



TRIPLE-GROOVE ELECTRIC CLUTCH

Start and stop the auger without shutting down the gas engine drives.

| AUGER SPECIFICATIONS |   |
|----------------------|---|
| TROUGH GAUGE         | 12 GA   |
| TROUGH CONNECTORS    | ¼" FLANGE                                       |
| MAIN FLIGHTING       | 10" OD X 7 GA STRETCHED + WELDED                |
| INTAKE FLIGHTING     | 10" OD X 7 GA WELDED WITH WEAR EDGE TECHNOLOGY™ |
| FLIGHTING SHAFT      | 2" OD X 0.120" WALL TUBING                      |
| DRIVESHAFT           | 1 - ½" OD X 10 GA TUBING                        |
| DRIVESHAFT BEARINGS  | 1 - ½" OIL IMPREGNATED HARDWOOD BEARINGS        |
| TRACK                | HIGH YIELD 11 GA ROLL FORMED                    |
| TRACK SHOE           | 2 - ¾" STEEL ROLLER                             |
| UNDERCARRIAGE        | 3" SQUARE TUBING                                |
| AXLES                | 2 - ½" SQUARE TUBING                            |
| HUB & WHEELS         | 4 BOLT AGRICULTURAL TYPE HUBS, 15" WHEEL        |
| LIFT CABLE           | ¼" AIRCRAFT TYPE GALVANIZED STEEL CABLE         |
| TIRES                | 15 AGRICULTURAL TIRES                           |
| TOP DRIVE            | #80 ROLLER CHAIN & HARDENED STEEL SPROCKETS     |
| TOP DRIVE BEARINGS   | 1 - ¼" PILLOW BLOCK                             |
| WINCH                | REDUCTION GEAR WITH AUTOMOTIVE BRAKE            |
| GEARBOX              | FORMED STEEL GEARS WITH TAPERED ROLLER BEARINGS |
| WHEEL TREAD          | 96"   |
| GAS HORSE POWER      | 37 - 38   |
| CAPACITY             | 7,000 - 9,000 bph                               |




Heights measured from bottom of auger spout to ground.

|   |          |
|---|----------|
| A | 9' - 6"  |
| B | 14' - 1" |
| C | 18' - 1" |
| D | 14' - 5" |
| E | 14' - 3" |
| F | 13' - 9" |
| G | 11'      |

| DISCHARGE CLEARANCE DIMENSION |          | TRANSPORT DIMENSION |          |
|-------------------------------|----------|---------------------|----------|
| MIN                           | 9' - 6"  | LENGTH              | 45' - 6" |
| MAX                           | 18' - 1" | WIDTH               | 8'       |
| HEIGHT                        | 10' - 6" | HEIGHT              | 10' - 6" |

| WEIGHT                   |           |
|--------------------------|-----------|
| HITCH WEIGHT (W/ ENGINE) | 472 lbs   |
| TOTAL WEIGHT (W/ ENGINE) | 3,058 lbs |

| SPECIFICATION |       |
|---------------|-------|
| BELT SIZE     | 3B270 |



AGI is a leading provider of equipment solutions for agriculture bulk commodities including seed, fertilizer, grain, and feed systems with a growing platform in providing equipment and solutions for food processing facilities. AGI has manufacturing facilities in Canada, the United States, the United Kingdom, Brazil, South Africa and Italy and distributes its products globally.



Box 39, 74 Main Street, Rosenort, Manitoba, Canada R0G 1W0  
1.866.467.7207 | [sales@grainaugers.com](mailto:sales@grainaugers.com)

[AGGROWTH.COM](http://AGGROWTH.COM)

[in](#) [f](#) [t](#) [@](#) [@aggrowthintl](#)

# UTX

## U-Trough Auger



| FEATURE  | ADVANTAGE   | BENEFIT  |
|--|---|--|
| <b>TRIPLE BANDED BELTS</b>                                       | Triple banded belts maintain speed by providing better tension  | Less slippage will help you get the job done fast  |
| <b>WEAR EDGE TECHNOLOGY™</b>                                     | Extra layer of welded steel on critical wear points extends the life of the flighting   | Flighting lasts longer and needs to be replaced less often – saving time and money   |
| <b>TOP DRIVE CHAIN TENSIONER</b>                                 | Provides better adjustment capabilities and provides consistent chain drive tension   | Adjusts easily and improves the life of the drive chain, saving you time and money   |
| <b>HOSE ROUTING</b>  | Fully enclosed hose routing   | Provides a cleaner sleeker look and protects the hoses from the elements   |
| <b>SELF-LEVELING MOTOR</b>                                       | Belts maintain proper tension at all heights  | Spend less time adjusting tension so you can get the job done fast   |
| <b>ROUND DISCHARGE SPOUT</b>                                     | Fits most poly bucket spouts  | Directs grain to center of the truck box better than square version  |
| <b>POWDER COAT PAINT</b>   | Stronger, longer lasting finish   | Looks brand new for longer and prevents rust   |
| <b>WORK LIGHTS</b>   | LED lights illuminate the equipment in low-light situations   | Added light helps you work after dusk, while providing easier alignment with the bin and truck. Added visibility when filling also helps to avoid unnecessary spillage |
| <b>U-TROUGH DESIGN</b>   | Delivers a higher capacity of up to 9,000 bph   | Keeps up with your biggest jobs while saving you time with every truckload   |
| <b>REMOVEABLE TOW BAR</b>  | Tow bar can be connected when towing the auger and disconnected when not in use   | Added maneuverability lets you quickly and easily tow your auger from one area to another  |
| <b>SOLID TUBE GUARD</b>  | Driveline is completely enclosed by a solid tube guard  | Protects the driveline from the elements, preventing wear  |
| <b>FLIGHT CONNECTIONS</b>  | Square one-bolt flight connections maintain proper alignment throughout use   | Smoother operation with no need to realign, saving you time  |
| <b>DRIVESHAFT AND BEARING</b>                                    | Constructed out of oil impregnated hardwood   | Quieter operation and longer lasting material  |
| <b>REVERSING GEARBOX</b>   | Comes with shifting linkage and lockout   | Safely reverse the auger at all angles   |
| <b>COLLAPSING SPRING LOADED HOPPER EXTENSION</b>                 | Can easily fit under bin unloads and hopper bins  | Less spillage and conveniently designed to work with all of your existing bins and unloads   |
| <b>SELF-PROPELLED MOVER KIT WITH JOYSTICK HYDRAULIC STEERING</b> | Self-propelled four-wheeled steering and hydraulic joystick controls offer minimal driving effort and rugged all-terrain tires to help the auger maneuver through uneven or soft ground | Setting up at bins and moving around the yard will be fast and easy so you can get the job done in less time   |
| <b>TRIPLE-GROOVE ELECTRIC CLUTCH</b>                             | Start and stop the auger without shutting down the gas engine drives  | Quickly and easily stop the auger without shutting down the engine   |
| <b>44-LITER GAS TANK</b>   | Increased tank size allows more gas to be stored on the auger   | Lets you work as long as you need to in order to get the job done  |
| <b>DISCHARGE HEIGHT</b>  | AGI's UTX U-Trough Auger reaches a discharge height of 18' 1"   | Outreaches competitor discharge heights, with the competing model only reaching 16'  |